



ATTENTION: PLEASE READ

Date: January 12, 2021


Bulletin #: Bul-Prod-121-007

Subject: **NEW and Superseded Unwelded Driveshaft Kits**


To: All Neapco Customers

NEW Neapco Unwelded Driveshaft Kits:

We are pleased to introduce our new Neapco OE Series versions of (4) popular genuine Neapco unwelded assemblies. These each feature a 36" DOM tube pre-welded to a Neapco OE Series double cardan assembly.



Type 7



Type 8

New Neapco Part#	Driveshaft Style	Fitment @ Axle	Fitment @ Transfer Case
N909365G-3600	Type 7, Half-Round	1310 U-Joint	1310 Half-Round Dbl Cardan Assembly
N921050G-3600	Type 8, Flanged	1330 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole
N921050G-3607	Type 8, Flanged	1350 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole
N921050G-3603	Type 8, Flanged	3R U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole

New Superseded Unwelded Driveshaft Kits:

We are also pleased to announce Neapco has lengthened all Unwelded Driveshaft Kits for the popular front driveshaft applications. The standard 36" and 54" DOM tube lengths allow greater application coverage, especially on lifted trucks. These products improve shop productivity and efficiency by reducing build and prep time. Simply cut the pre-welded tube to length, fit and weld the slip assembly, final balance, and install. All the parts required are pre-assembled and ready to weld.

Please see the attached chart and images for additional product details, including:

- Old Part number to New Part number interchange
- Driveshaft Style
- Fitment at Axle
- Fitment at Transfer Case
- Tube Diameter and Thickness
- Universal Joint Style
- Extended Length
- Compressed Length










ATTENTION: PLEASE READ

THE DRIVELINE EXPERTS

OLD Neapco Part#	New Neapco Part#	Driveshaft Style	Fit @ Axle	Fit @ Transfer Case	Tube	UJ Style	Extended Length	Compressed Length
N921052-3000	N921052-3600	Type 8, Flanged DC	1350 U-Joint	Flange, (4x) M12x1.75 Thru, 4.25" B.C., 2" Pilot Hole	2.750 X 0.083	Body (Cross) Lubeable	54.34	50.5
N921052G-3000	N921052G-3600	Type 8, Flanged DC	1350 U-Joint	Flange, (4x) M12x1.75 Thru, 4.25" B.C., 2" Pilot Hole	2.750 X 0.083	Maintenance Free	54.34	50.5
N924141G-2013	N924141G-3613	Type 14	1410 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.500 X 0.120	Maintenance Free	53.55	52.05
S91397-2002	S91397-3602	Type 8, Flanged DC	7290 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.000 X 0.120	Body (Cross) Lubeable	53.06	50.12
N909365-2600	N909365-3600	Type 7, Half-Round DC	1310 U-Joint	1310 Half-Round Dbl Cardan Assembly	2.000 X 0.120	Body (Cross) Lubeable	55.94	52.84
S91397-2000	S91397-3600	Type 8, Flanged DC	1310 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.000 X 0.120	Body (Cross) Lubeable	53.38	50.28
N131138-3000	N131138-3600	Type 9, DC w/Stub	3R U-Joint	NV 246 Splined Stub for Front Driveshaft (Many GM AutoTrac® 1999-2007 GM models)	2.000 X 0.120	Body (Cross) Lubeable	49.81	—
S91397-2001	S91397-3601	Type 8, Flanged DC	7260 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.000 X 0.120	Body (Cross) Lubeable	53.38	49.95
S91397-2003	S91397-3603	Type 4, Single Cardan	3R U-Joint	3R Universal Joint	2.750 X 0.065	Body (Cross) Lubeable	48.56	45.44
N909363-2600	N909363-3600	Type 7, Half-Round DC	1310 U-Joint	1310 Half-Round Dbl Cardan Assembly	2.500 X 0.083	Body (Cross) Lubeable	58.32	54.19
N909363G-2600	N909363G-3600	Type 7, Half-Round DC	1310 U-Joint	1310 Half-Round Dbl Cardan Assembly	2.500 X 0.083	Maintenance Free	58.32	54.19
N911818-2600	N911818-3600	Type 7, Half-Round DC	1330 U-Joint	1330 Half-Round Dbl Cardan Assembly	2.500 X 0.083	Body (Cross) Lubeable	52.91	48.75
N921056X-2000	N921056X-3600	Type 8, Flanged DC	1330 U-Joint	Flange, (4x) 0.49" Thru Holes, 3.938" (100mm) B.C., 2.162" Pilot Hole	2.500 X 0.095	Body (Cross) Lubeable	52.02	49.35
N921050-2000	N921050-3600	Type 8, Flanged DC	1330 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.500 X 0.095	Body (Cross) Lubeable	54.06	51.18
N921050G-2010	N921050G-3610	Type 14, Booted Yoke Shaft	1350 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.500 X 0.095	Maintenance Free	52.95	51.45
N921050-2007	N921050-3607	Type 8, Flanged DC	1350 U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.500 X 0.095	Body (Cross) Lubeable	54.06	51.18
N921050-2003	N921050-3603	Type 8, Flanged DC	3R U-Joint	Flange, (4x) 0.46" Thru Holes, 4.25" B.C., 3-1/8" Pilot Hole	2.500 X 0.095	Body (Cross) Lubeable	53.94	51.44
N921054-4800	N921054-5400	Type 8, Flanged DC	1350 U-Joint	Flange, (4x) M12x1.75 Thru, 4.25" B.C., 2.68" (68mm) Pilot Hole	3.500 X 0.083	Body (Cross) Lubeable	72.16	68.91
N921054-4801	N921054-5401	Type 8, Flanged DC	1410 U-Joint	Flange, (4x) M12x1.75 Thru, 4.25" B.C., 2.68" (68mm) Pilot Hole	3.500 X 0.083	Body (Cross) Lubeable	72.70	69.26



NeapcoParts.com includes all the most current information about our products, including those listed above

As always, we thank you for your continued support of genuine Neapco products. Please contact your respective Neapco Regional Sales Manager for pricing and any additional questions you might have.

Chris Creager

Product Manager – Neapco Drivelines Aftermarket Group



New England Auto Products Corporation U.S.A. since 1921
 Neapco.com/aftermarket E-catalog/order portal: NeapcoParts.com

Important Bulletin from Neapco Drivelines Aftermarket Group